

Product Specification

CO0W-20 Fully-Synthetic Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO0W20-1	CO0W20-4	CO0W20-5	CO0W20-20	CO0W20-60	CO0W20-200

LEVELS OF QUALITY

The lubricant CO0W-20 complies with the following international specifications:

API SN, ACEA C2, A1/B1, VOLVO VCC RBSO-2AE, GM DEXOS 01, FORD WSS-M2C947-A, FIAT 9.55535-DSX/GSX, BMW LL-14 FE+, ILSAC GF-5, CHRYSLER MS-6395, GM2_6094M

DESCRIPTION

CO0W-20 is a Lubricant specially designed for highly stressed downsized engines with maximum power output, for extreme fuel economy characteristics and reduced CO₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves.

Due to its characteristics CO0W-20 is predominantly used in Euro 5/6 engines where an ACEA A1/B1 engine oil is specified. CO0W-20 has been specially developed and approved for use in the new VOLVO VEA (Volvo Engine Architecture) engine generation. As CO0W-20 will be our basis for new engine designs good biofuel compatibility is provided.

SAE Scale		0W-20
Density at 15°C.Kg./dm ³	ASTM D1298	0.838
Viscosity at 100°C.cSt	ASTM D445	8.5
Viscosity Index	ASTM D2270	155
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-42
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	8.0

The above mentioned values are indicative of production average values and are not an integral part of the specification.

TDS Comline 0W-20_REV.2 March 2020